

E. ROKO Dry-Erase White Laminate

Recommended Uses: E.Roko Dry-Erase Laminates are recommended for interior vertical applications. Possible uses are wall coverings, class rooms, office furniture, children's furniture or any area that needs a high quality writable surface with magnetic properties.

Sheet sizes: 4' x 8'

Thickness Available: 1.0mm thickness (.040")

Colours: White

Also available: • Magnetic Non-Ghosting Dry-Erase Marker Board
• Tackboard

Tricks & Tips

Removing Permanent Marker

Ever accidentally use a permanent marker on an E. Roko dry-erase board?

Don't despair! Take a DRY-ERASE marker and scribble back and forth

over the permanent marker and erase it all. The permanent marker lifts off too!




GREENGUARD Certified Adhesives



Choice Brands Adhesives - XA-2600™ - Cold / Hot Press Glue

- PVA Adhesive
- General Purpose Cold Press Adhesive; For Hot and Cold Press applications
- Green Guard Certified, LEED 3.2, 4.1, 4.4 Compliant, California Compliant
- Open time - 10 minutes, press time - 30 minutes
- Available in 5, 55 gallons and totes



Titebond VOC-Compliant Heavy Duty Construction Adhesive

is a versatile adhesive that exceeds the APA's AFG-01 specification.

It is designed for a wide range of construction applications including wet, frozen and treated lumber.

It is also ideal for metal, brick, concrete, ceramics and most large panel-type substrates.

Titebond VOC-Compliant Heavy Duty fills gaps and irregularities between materials and provides a more solid backup surface. It reduces the amount of nailing and helps eliminate squeaky floors.

It also offers excellent water-resistance and remains permanently flexible.

STA'-PUT SP-80 - Spray Contact

is a solvent-based, low VOC, non-chlorinated contact adhesive specifically formulated for bonding high pressure laminate to particleboard and many other porous & non-porous surfaces. SP-80 provides high solids, and a water resistant bond, and also exhibits high strength, aggressive grab, and quick tack. SP-80 is also available in an aerosol can for Laminate Repair and Edgbanding. This product is also available in a canister system that provides a smooth spray pattern and reduces telegraphing on thin laminates.



Z Solvent Free Postformable Water Based Contact Adhesive

is a high strength contact adhesive specifically designed to bond a wide variety of substrates in woodworking, laminating, and many other applications. Z provides excellent initial and ultimate bond strengths as well as exceptional heat resistance. Z is ideal for postforming operations, and combines zero flammability with zero VOC's, zero Methylene Chloride and zero HAPS.